

IN THE CLAIMS:

This **Listing of Claims** will replace all prior versions, and listings, of claims in the application:

Listing of Claims

1. (previously presented) A pulse valve (10) with a closing body (18) that cooperates with a valve seat (22) by at least a valve spring (24) and, in a first switching position, establishes a flow connection between a supply channel (12) and a discharge channel (14) and, in a second switching position, blocks the flow connection, the closing body (18) periodically moving in a reciprocating motion (82) between the two switching positions during an actuation of the pulse valve (10), wherein a hydraulic damping to a movement of the closing body (18) by a throttle gap (70) occurs in a damped range (62),

wherein the closing body (18) is connected via a rod (56) with a damping disk (54) made of structural material, the damping disk (54) provided in a damping cylinder (50) that is open on a first end face and, except for a guide opening (58), in which the rod (56) is guided, closed on a second end face being located opposite to the first end face, and

wherein the damping disk (54) exits the damping cylinder (50) shortly before the closing body reaches the second switching position.

2. (previously presented) The pulse valve (10) as recited in claim 1, wherein the reciprocating motion progresses from the first switching position to the second switching position sequentially through the damped range, a transition region (66), and an undamped range (64) that extends for approximately 0.5 millimeters before the closing body reaches the second switching position.

3. (previously presented) The pulse valve (10) as recited in claim 1, wherein a bypass (90) extending in parallel with the throttle gap (70) is actuated to open along the undamped range (64).

4. (previously presented) The pulse valve (10) as recited in claim 2, wherein the throttle gap expands during the transition region as the reciprocating motion progresses towards the second switching position.

5. (previously presented) The pulse valve (10) as recited in claim 4, wherein the hydraulic damping is attained again when the damping disk re-enters the damping cylinder (50).

6. (original) The pulse valve (10) as recited in claim 4, wherein the flow cross section of the damping cylinder (50) expands continually at its open end.

7. (original) The pulse valve (10) as recited in claim 6, wherein the damping cylinder (50) includes an inner chamfer (68) at its open end.

8. (previously presented) The pulse valve (10) as recited in claim 6, wherein the damping cylinder (50) includes at least one inner groove (72) and/or recess (74, 78) at its open end that expand in the direction toward the open end face.

9. (previously presented) The pulse valve (10) as recited in claim 8, wherein the flanks of the groove (72) and the contour (76, 80) of the recess (74, 78) have a bent shape.

10. (previously presented) The pulse valve (10) as recited in claim 4, wherein the damping cylinder (50) includes an inner annular groove (84), the width of which is greater than the thickness of the damping disk (50) at its circumference.

11. (previously presented) The pulse valve (10) as recited in claim 10, wherein the flanks of the annular groove (84) are transition regions (66).

12. (previously presented) The pulse valve (10) as recited in claim 1, wherein the damping disk (54) includes an axially projecting edge (88) around its circumference.

13. (previously presented) The pulse valve (10) as recited in claim 1, wherein the damping disk (54) has a surface that is not circular.

14. (previously presented) The pulse valve (10) as recited in claim 1, wherein the damping disk (54) is very thin and has a fine, perforated structure.

15. (previously presented) The pulse valve (10) as recited in claim 14, wherein the cross section of holes (94) of the fine, perforated structure is in the micrometer range.

Claims 16-19 cancelled.

20. (previously presented) The pulse valve (10) as recited in claim 14, wherein the fine-meshed network structure forms a mesh with the cross section in a micrometer range.

Claim 21 cancelled.

22. (currently amended) The pulse valve (10) as recited in claim 12, wherein the undamped ~~par~~range (64) ~~of the reciprocating motion (82) is formed by a~~ passage (98, 100) between the valve stem (26) or the rods (56) connected therewith rod (26) and the damping disk (54) ~~and the diaphragm (96).~~

23. (currently amended) The pulse valve (10) as recited in claim 1, wherein the damping disk (54) ~~and the diaphragm (96) are~~is coaxial with the valve stem~~rod~~ (26) in the direction of flow in front of or behind the closing body (18).

24. (previously presented) The pulse valve (10) as recited in claim 1, wherein a surface of the damping disk (54) is larger than a cross section of the closing body (18).